



NK-48A

DESCRIPTION:

This product is suitable for the junction box of the FTTH network inside buildings, used as an optical interconnection point between the optical cables of the operator's power or distribution network and the building's (vertical) distribution network.

FEATURES:

1. Water-proof design with IP-65 Protection level.
2. Impact test:IK08,Pull Force:1000N,Full rugged design.
3. Independent fiber optic cable fusion area, independent fiber optic wiring area, without mutual interference during operation.
4. Fiber bend radius control more than 40mm.
5. Can install and accommodate up to 3 pre 1:16 box optical splitters of box size 45x100x10mm.
6. 1 mid-span cable entrance (10-16.5mm) for uncut cable and 2 Mechanical glands for distribution cable (8-16.5mm).
7. 48 adaptors for drop cable patching.
8. Multiple boxes can be stacked and installed to increase wiring usage.

CONFIGURATION

Material	Dimension L*W*H (mm)	Max Capacity	Number and size of cable entries	Adapter	Box optical splitters	Color
PC+ABS	450*150*180	Splice 96 Fibers (6 trays,16 fiber/tray)	1 X Oval port , Ø 8-16mm 2 X Round port , Ø 8-18mm	48	3 X 1:16 (45*100*10mm)	Grey Customized
Carton size(mm)		QTY	Weight(kg)	Net weight(kg)		Gross weight(kg)
560*495*450		6	2.47	16.50		18.00